




- FRL
- AC, BC
- AFC, BFC
- AF, BF
- AR, BR
- AFR, BFR
- AL, BL
- JAC
- JAF
- JAR
- JAW**
- JAL
- PTH
- JAD

Ordering Code

| JA | W | 4000 | 04 | D | N |
|------------|--------------------|---------------|--------------|---------------------------------------|---------------------------------|
| Series | Function | Specification | Port size | Drain Type | Wiring Form |
| JAW2000-02 | Filter & Regulator | 1000 | M5: M5 x 0.8 | Blank: Semi-automatic D: Automatic | Blank: Standard N: Metal cup |
| JAW3000-03 | | 2000 | 01: G 1/8" | | |
| | | 3000 | 02: G 1/4" | | |
| | 4000 | 03: G 3/8" | | | |
| | 5000 | 04: G 1/2" | | | |
| | | | 06: G 3/4" | | |
| | | | 10: G 1" | | |

Symbol



Specification

| Model | JAW1000-M5 | JAW2000-01 | JAW2000-02 | JAW3000-02 | JAW3000-03 | JAW4000-03 | JAW4000-04 | JAW4000-06 | JAW5000-06 | JAW5000-10 |
|------------------------------|--------------------|------------|------------|-------------------------------------|------------|------------|------------|------------|------------|------------|
| Rated Flow | 100 | 550 | 550 | 2000 | 2000 | 4000 | 4000 | 4500 | 5500 | 5500 |
| Port Size | M5 | 1/8 | 1/4 | 1/4 | 3/8 | 3/8 | 1/2 | 3/4 | 3/4 | 1 |
| Filter Precision | 25 µm | | | | | | | | | |
| Max. Adjustable Pressure | 1.0 MPa | | | | | | | | | |
| Ensured Pressure Resistance | 1.5 MPa | | | | | | | | | |
| Operating Temperature Range | 5 ~ 60 °C | | | | | | | | | |
| Range of Adjustable Pressure | 0.05 ~ 0.7 MPa | | | 0.05 ~ 0.85 MPa | | | | | | |
| Container Material | Poly Carbonate | | | | | | | | | |
| Container Cup | Not Available | | | | Iron | | | | | |
| Drain Function | Differential Drain | | | Differential Drain, Automatic Drain | | | | | | |
| Valve Type | With Overflow | | | | | | | | | |